

GRIGGS PAINT -- TT-P-1757B ZINC CHROMATE PRIMR -- 8010-00-515-2211

=====
Product Identification
=====

Product ID:TT-P-1757B ZINC CHROMATE PRIMR

MSDS Date:01/01/1998

FSC:8010

NIIN:00-515-2211

Status Code:A

MSDS Number: CLLJQ

=== Responsible Party ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

City:PHOENIX

State:AZ

ZIP:85040

Country:US

Info Phone Num:602-243-3293

Emergency Phone Num:800-42

4-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:58963

=== Contractor Identification ===

Company Name:GRIGGS PAINT

Address:3602 S 16TH PLACE

Box:City:PHOENIX

State:AZ

ZIP:85040

Country:US

Phone:602-243-3293

CAGE:58963

=====
Composition/Information on Ingredients
=====

Ingred Name:XYLENE

CAS:1330-20-7

RTECS #:ZE2100000

< Wt:7.

ACGIH TLV:434 MG/M3;100 PPM

ACGIH STEL:651 MG/M3;150 PPM

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE

CAS

:67-64-1
RTECS #:AL3150000
< Wt:4.
OSHA PEL:2400 MG/M3;1000 PPM
ACGIH TLV:1780 MG/M3;750 PPM
ACGIH STEL:2380 MG/M3;1000 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:POTASSIUM ZINC CHROMATE YELLOW
CAS:37300-23-5
RTECS #:GE4600000
= Wt:27.
ACGIH TLV:0.01 MG/M3

Ingred Name:ALKYD RESIN SOLUTION
< Wt:2.

Ingred Name:MAGSIL 2628
CAS:14807-96-6
RTECS #:WW2710000
< Wt:5.
OSHA PEL:SEE TABLE Z-3
ACGIH TLV:2 MG/M3

Ingred Name:N-BUTYL ALCOHOL
CAS:71-36-3
RTECS #:EO1400000
< Wt:1.

OSHA PEL:300 MG/M3;100 PPM
ACGIH STEL:C152 MG/M3;C50 PPM
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:DIRECT CONTACT TO EYES MAY CAUSE
IRRITATION. PROLONGED AND/OR REPEATED CONTACT MAY CAUSE SKIN
IRRITATION. INHALATION OF HIGH CONCENTRATIONS OF VAPORS MAY LEAD TO
LUNG CHANGES, NAUSEA, VOMITING, COUGH, PU

LMONARY IRRITATION, AND

CENTRAL NERVOUS SYSTEM DEPRESSION. INGESTION MAY CAUSE GASTROINTESTINAL DISTURBANCES.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: HIGH VAPOR MAY CAUSE DROWSINESS, DIZZINESS FATIGUE, FOLLOWED BY COMA. EYE: DIRECT CONTACT AND/OR CONTACT WITH VAPORS MAY CAUSE IRRITATION. SKIN: PROLONGED AND/OR CONTACT MAY CAUSE IRRITATION AND/OR DERMATITIS. INGESTION GASTROINTESTINAL DISTURBANCES.

Medical Cond Aggravated by Exposure:INDIV

IDUALS WITH PRE-EXISTING

DISEASES IN OR HISTORY OF AILMENTS INVOLVING SKIN CENTRAL NERVOUS SYSTEM, LIVER AND KIDNEY.

=====
First Aid Measures
=====

First Aid:EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. SEEK MEDICAL AID.SKIN: WASH THOROUGHLY WITH SOAP AND WATER. SEEK MEDICAL AID IF IRRITATION PERSISTS.INGESTION: IMMEDIATELY SEEK MEDICAL A ID.

=====
Fire Fighting Measures
=====

Flash

Point Method:TCC

Flash Point:=-20.C, -4.F

-4 DEG F.

Autoignition Temp:Autoignition Temp Text:NONE

Lower Limits:1.0%

Upper Limits:NONE

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:APPROVED GAS MASK REQUIRED FOR FIRE FIGHTING PERSONEL. WATER MAY BE INEFFECTIVE. WATER MAY BE USED TO COOL CONTAINERS. IF WATER IS USED, FOG NOZZLES ARE PREFERRED.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS, AND OPEN FLAME.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:STOP LEAK IF NO RISK INVOLDED. REMOVE ALL SOURCES OF IGNITION. STAY UPWIND. ABSORB WITH INERT MATERIAL. FLUSH AREA WITH WATER.

Neutralizing Agent:NONE.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED AND UP RIGHT TO PREVENT LEAKAGE. AVOID FL

AMES, WELDING, OPEN LIGHTS, ETC. AVOID

BREATHING OF VAPOR AND SPRAY MIST. AVOID SKIN AND EYE CONTACT.

Other Precautions: MAINTAIN GOOD HYGIENE. DO NOT USE IN CONFINED AREAS,
TANK OR PIT, WITHOUT ADEQUATE VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION
EXPOSURES BELOW (PEL), USE MSHA/NIOSH APPROVED UNITS. USE UNITS PER
CURRENT 29 CFR 1910.134 AND FOLLOW MANUFACTURERS' INSTRUCTIONS
AND

WARNINGS. IF WITHIN O SH PROTECTION FACTOR, AIR PURIFYING OV/FILTER
UNITS OK FOR USE.

Ventilation: LOCAL AND MECHANICAL EXHAUST.

Protective Gloves: RUBBER GLOVES.

Eye Protection: SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES.

Other Protective Equipment: EYE BATH AND SAFETY SHOWER.

Work Hygienic Practices: MAINTAIN GOOD HYGIENE. DO NOT USE IN CONFINED
AREAS WITHOUT ADEQUATE VENTILATION.

Supplemental Safety and Health

NONE

=====
===== Physical/Chemical Properties =====

==

Boiling Pt: B.P. Text: 131 TO 280 DEG F.

Melt/Freeze Pt: M.P/F.P Text: NONE

Decomp Temp: Decomp Text: NONE

Vapor Density: HEAVIER

Spec Gravity: (H2O=1): 1.3

VOC Pounds/Gallon: 378

VOC Grams/Liter: 3.16

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: ESSENTIALLY NIL.

Appearance and Odor: VISCOUS LIQUID WITH TYPICAL PAINT ODOR.

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS.

Stability Condi

on to Avoid:FLAMES, SPARKS, SMOKING AND HEAT.

Hazardous Decomposition Products:CARBON MONOXIDE AND CARBON DIOXIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:USE INERT ABSORBENT MATERIALS ON SPILLS.DISPOSE
OF IN ACCORDANCE WITH ALL FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements

of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.