View NSN Online: https://aerobasegroup.com/nsn/8030-01-105-8625

THE DEXTER CORPORATION -- PROPRIETARY BLEND FREKOTE 1711 AEROSOL SILICONE SOLUTION -- 8030-01-105-8625

Product ID:PROPRIETARY BLEND FREKOTE 1711 AEROSOL SILICONE SOLUTION

MSDS Date:04/21/1995 FSC:8030 NIIN:01-105-8625 Status Code:A **MSDS Number: CLLSG** === Responsible Party === Company Name: THE DEXTER CORPORATION Address:ONE DEXTER DRIVE City:SEABROOK State:NH ZIP :03874 Country:US Info Phone Num:603-474-5541 Emergency Phone Num:1-800-424-9300 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:04373 === Contractor Identification === Company Name: THE DEXTER CORPORATION Address: ONE DEXTER DRIVE Box:City:SEABROOK State:NH ZIP:03874 Country:US Phone:603-474-5541 CAGE:04373

Ingred Name:STODDARD SOLVENT CAS:8032-32-4 Code:F RTECS #:OI6180000 Minumum % Wt:1. Maxumum % Wt:3. O SHA PEL:100 PPM ACGIH TLV:1370 MG/M3;300 PPM

Ingred Name:ALIPHATIC HYDROCARBON CAS:64742-48-9 Code:F Minumum % Wt:76. Maxumum % Wt:78. OSHA PEL:400 PPM ACGIH TLV:200 PPM

Ingred Name:SILICONE BLEND &It; Wt:10.

Ingred Name:PROPANE CAS:74-98-6 RTECS #:TX2275000 = Wt:14.81 OSHA PEL:1800 MG/M3;1000 PPM

Effects of Overexposure:CAN CAUSE EYE IRRITATION. PROLONGED OR REPEATED CONTACT CAN CAUSE SKIN IRRITATION. CAN BE IRRITATIN

G TO THE

RESPIRATORY SYSTEM.EXCESSIVE EXPOSURE CAN CAUSE DIZZINESS, NAUSEA, HEADACHES, AND OTHER CENT RAL NERVOUS SYSTEM EFFECTS.

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. SKIN: FLUSH AFFECTED AREA WITH WATER IMMEDIATELY. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING.

Flash Point: NONE Autoignition Temp:Autoignition Temp Text:NONE Lower Limits:NONE Upper Limits:NONE Extinguishing Media:FOAM, DRY CHEMICAL OR CO2. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES. Unusual Fire/Explosion Hazard:KEEP AWAY FROM HOT SURFACES.

Spill Release Procedures: CLEAR AREA. PROVIDE ADEQUATE VENTILATION. COLLECT WITH ABSORBENT AND PREVENT RUN-OFF.

## REMOVE ALL POTENTIAL IGNITION SOURCES. USE APPROPRIATE PROTECTIVE EQUIPMENT.

Handling and Storage Precautions: STORE AWAY FROM HEAT AND FLAME. USE WITH ADEQUATE VENTILATION. Other Precautions: AVOID CONTACT WITH SKIN AND BREATHING OF VAPORS. Respiratory Protection: IF USE CONDITIONS GENERATE AIRBORNE CONTAMINATION, USE NIOSH RECOMMENDED RESPIRATORS APPROPRIATE FOR THE AIRBORNE LEVELS GENERATED. Ventilation: AS REQUIRED TO CONTROL AIRBORNE CONTAMINATION. Protective Gloves:SOLVENT RESISTANT. Eye Protection: CHEMICAL SPLASH GOGGLES. Other Protective Equipment: USE IMPERVIOUS CLOTHING IF NECESSARY TO AVOID SKIN CONTACT. Work Hygienic Practices:NONE Supplemental Safety and Health NONE Boiling Pt:B.P. Text:NONE

Melt/Freeze Pt:M.P/F.P Text:NONE Decomp Temp:Decomp Text:NON E Vapor Pres:(MM HG) @23 C 2068-2327 Vapor Density:3.17 Spec Gravity:0.68+-0.02 Evaporation Rate & amp; Reference:5 (N-BUTYL ACETATE=1) Solubility in Water:INSOLUBLE Appearance and Odor:COLORLESS SLIGHT ODOR Percent Volatiles by Volume:95.8%

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIAL CAN CAUSE A REACTION. Stability Condition to Avoid:NONE Hazardous Decomposition Products:MAY YIELD INCOMPLETELY BURNED CARBON

## PRODUCTS. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL LAWS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and di

sclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.