

BOSTIC S.A. -- VINYCOL 1520 POLYURETHANE GLUE -- 8040-01-368-4643

===== Product Identification =====

Product ID:VINYCOL 1520 POLYURETHANE GLUE

MSDS Date:01/01/1994

FSC:8040

NIIN:01-368-4643

Status Code:A

MSDS Number: CLQRD

=== Responsible Party ===

Company Name:BOSTIC S.A.

Address:R.N. 19 77170 COUBERT

City:COUBERT

Country:FR

Info Phone Num:800-626-7225 (33) 1 64 92 12 1

Emergency Phone Num:800-4

24-9300

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:F2857

=== Contractor Identification ===

Company Name:BOSTIC S.A.

Address:R.N. 19 77170 COUBERT

Box:City:COUBERT

Country:FR

Phone:800-626-7225 (33) 1 64 92 12 1

CAGE:F2857

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE

= Wt:3.

ACGIH TLV:100 PPM

Ingred Name:DMF

= Wt:2.

ACGIH TLV:10 PPM

Ingred Name:MEK

= Wt:25.

ACGIH TLV:200 PPM

Ingred Name:ACETONE

= Wt:50.

ACGIH TLV:1000 PPM

Ingred Name:POLYURETHANE

= Wt:20.

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:DERMAL IRRITATION. EFFECTS OF OVER EXPOSURE ARE NARCOTIC.

Effects of Overexposure:IRRITATING TO SKIN, EYES AND RESPIRATORY TRACT.

===== First Aid Measures =====

First Aid:BREATHE FRESH AIR. IN CASE OF CONTACT

WITH SKIN, EYES WASH

IMMEDIATELY WITH ABUNDANT SOAP AND WATER, SEE A DOCTOR IMMEDIATELY IF INGESTED.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:=-17.C, 1.4F

Lower Limits:2.5%

Upper Limits:12.5%

Extinguishing Media:CO2, FOAM, POWDER.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP AWAY FROM FIRE. AVOID SPILLING AND DRIPPING. MOP UP WITH ABSORBENT MATERIALS (SAND, SAWDUST)

. RESIDUE

MUST BE KEPT IN A TIGHTLY CLOSED DRUM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED.

Protective Gloves:YES.

Eye Protection:YES.

Work Hygienic Practices:WASH HANDS AFTER USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt.=56.C, 132.8F

Vapor Pres:180 MBAR (AT 20 DEGREES C

Vapor Density:3

Spec Gravity:0.83

Evaporation Rate & Reference:500

Solubility in Wat

er:PARTIALLY

Appearance and Odor:OPALESCEMENT-SOLVENT SMELLING

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:OVERHEATING.

Hazardous Decomposition Products:CO, CO2 HCN.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE WASTES IN AN APPROVED PLACE.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.