

PRC-DESOTO INTERNATIONAL, INC, A PPG INDUSTRIES CO -- POLYTHIOETHER POLYMER  
COMPOUND PR-1826 B-1/2 -- 8030-01-290-5136

=====  
Product Identification  
=====

Product ID:POLYTHIOETHER POLYMER COMPOUND PR-1826 B-1/2

MSDS Date:11/08/1993

FSC:8030

NIIN:01-290-5136

Status Code:A

Kit Part:Y

MSDS Number: CLRXG

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL, INC, A PPG INDUSTRIES CO

Address

s:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060 / 800-228-5635

Emergency Phone Num:800-228-5635

Preparer's Name:ERNEST CARTER

Chemtrec Ind/Phone:(800)424-9300

CAGE:1LFF4

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC, A PPG INDUSTRIES CO

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060 / 800-228-5635

CAGE:1LFF4

=====  
Composition/Information on Ingre  
dients  
=====

Ingred Name:NATURAL CALCIUM CARBONATE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:20.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

&lt; Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:METHYL ETHYL KETONE

CAS:78-93-3

RTECS #:EL6475000

&lt; Wt:5.

=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNING, TEARING AND REDDENING. POSSIBLE TRANSIENT CORNEAL CLOUDING. SKIN: PROLONGED EXPOSURE MAY CAUSE REDNESS, BURNING, DRYING AND CRACKING OF SKIN. INHALATION: MAY CAUSE COUGHING, CHEST PAINS. THROAT IRRITATION. MAY CAUSE HEADACHES AND DIZZINESS, MAY BE ANESTHETIC AND MAY CAUSE OTHER CENTRAL NERVOUS SYSTEM EFFECTS. REVERSIBLE LIVER DAMAGE IS POSSIBLE AT HIGH DOSES. INGESTION: MAY CAUSE DROWSINESS, DIZZINESS, AND NAUSEA.  
Medical Cond Aggravated by Exposure:

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR, IF SYMPTOMS PERSIST, CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYSICIAN.

=====

===== Fire Fighting Measures =====

Flash Point Method:SCC  
Flash Point:65.6C, 150.F  
Lower Limits:1.8%  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER.  
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT.

===== Handling and Storage =====

Handling and Storage  
Precautions:WASH THOROUGHLY AFTER HANDLING AND BEFORE SMOKING OR EATING. AVOID INGESTION.  
Other Precautions:EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM. VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF T

LV,  
USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR.

Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL.

Protective Gloves:SOLVENT RESISTANT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:KEEP CONTAINER TIGHTLY CLOSED. DO NOT STORE ABOVE 120 DEG F. GROUNDING AND BONDING PROCEDURE SHOULD BE FOLLOWED WHEN TRANSPORTING THIS MATERIAL.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.

P. Text:175-175 DEG.F

Vapor Density:HEAVIER

Spec Gravity:1.45

VOC Pounds/Gallon:46

Appearance and Odor:BEIGE THIXOTOPIC PASTE.

Percent Volatiles by Volume:5.5%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE.

Conditions to Avoid Polymerization:WILL NOT OCCUR.

===== Disposal Considerations =====

=====

Waste Disposal Methods:EPA NO. D-035 HAZARDOUS WASTE. DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

===== Regulatory Information =====

State Regulatory Information:

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no m

anner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.